

Specification


VLAM series			Vacuum Angle Valve / Manually										
			Bellows STEM seal (A: SUS316L)										
Valve port		SIZE	16	25	40	50	63	80	100	160	200	250	320
Flange Standards	ISO-KF	KF	●	●	●	●	●	●	●	●	×	×	×
	ISO-K	KQ	×	×	×	×	●	●	●	●	×	×	×
	ISO-F	KC	×	×	×	×	●	●	●	●	×	×	×
Valve Actuating type			Manual acting										
Fluid			Vacuum in an inert gas system										
Operating temperature °C			≤120										
Operating pressure Pa (Abs)			1×10 ⁻⁶ ~ to atmospheric pressure										
Conductance L / s ^(Note 1)			7	14	42	95	150	250	520	1,430	-	-	-
Leakage Pa·m³/s	Inside	Standard material (FKM) 1.0×10 ⁻¹⁰ at room temperature (excluding gas permeation)											
	Outside	Standard material (FKM) 1.0×10 ⁻¹¹ at room temperature (excluding gas permeation)											
Main material			Body: SUS304, Bellows: [SUS316L] Main parts: SUS304, AL-6061, FKM (Standard seal)										
Open stroke			14	14	18	25	30	35	40	60	-	-	-
Number of Handle rotation			7	7	9	12.5	7.5	9	10	12			
Seal distance (A-Value)			40	50	65	70	88	90	108	138	-	-	-

(Note 1) Conductance is represented by "molecular flow" of elbow of the same dimension.


External dimension table

SIZE	16	25	40	50	63	80	100	160
A	40	50	65	70	88	90	108	138
B	135.5	143.5	170	188.5	264	280.5	325.5	459
C	48	48	60	69	-	-	-	-
D	Ø63	Ø63	Ø63	Ø63	Ø100	Ø100	Ø125	Ø200
F	-	-	-	-	Ø119	Ø119	Ø159	Ø208
H	Ø30	Ø40	Ø55	Ø75	Ø95	Ø114	Ø134	Ø190
J	-	-	-	-	Ø95	Ø110	Ø130	Ø180
K	-	-	-	-	Ø130	Ø145	Ø165	Ø225

Dimensional drawing







Internal detail



How to Order

Valve **V(A)B(C)** - ① ② - ③ - ④ - ⑤ ⑥ - (⑦)

Model VLAP - □□□ □□-□□ - □ - □□

Series	A Body shape	VLⒶC	L	L-type(Angle valve) 304SS Body												
		VYⒶC	Y	Y-type(Inline valve) 304SS Body												
	B Stem Seal	VⒶAC	A	316L Bellows STEM Seal												
		VⒶBC	B	AM350 Bellows STEM Seal												
		VⒶSC	S	O-Ring STEM Seal												
	C Operation type	VⒶBP	P	Double Acting (Pneumatic)												
		VⒶBS	S	Single Acting (N.C.)												
		VⒶBM	M	Manual operation												
		VⒶBQ	Q	Double Acting, w/Heater (Pneumatic)												
		VⒶBR	R	Single Acting, w/Heater (N.C.)												
		VⒶBH	H	Double Acting, Heating model(Pneumatic)												
		VⒶBK	K	Double Acting, Heating model, w/Heater(Pneumatic)												
		VLⒶD	D	Double Acting, w/Soft start bypass valve(Pneumatic)												
		VLⒶT	T	Single Acting, w/Soft start bypass valve(N.C.)												
		VLⒶX	X	Single Acting, w/Soft start integrated valve(N.C.)												
		VLⒶW	W	Bonnet gasket seal type, Double Acting (Pneumatic)												
		VLⒶY	Y	Bonnet gasket seal type, Single Acting (N.C.)												
		VLⒶZ	Z	Bonnet gasket seal type, Manual operation												
Port flange	Valve size	①	□□□	016	025	040	050	063	080	100	160	200	250	320		
	Flange Spec.	②	□□ Specific	KF		KQ		KC		CF		JF				
Seal material (Disc, Bonnet, Stem)	③ (Note 1)	□□	N1		ED	S1	FS	R1	R2	R3	P1	P2	U1			
			FKM	NBR	EPDM	VMQ	FFKM	Chemraz®	Chemraz®	Chemraz®	Kalrez®	Kalrez®	ULTIC ARMOR®			
			SS592		SS630		SSE38		4079		9100		UA4640			
			Im case of FFKM (FS), please specify a separate material.													
	CDA port position	④ (Note 2)	□ Branch port Lower part	None			E			S			W			
Rear				Right			Left			Same Direction						
																
Sensor	⑤	□	0			1			2							
	⑥	□	None			1 EA			2 EA							
Solenoid or Heater Mounting	⑦	(G) or (W)	C		N		P		H							
			W8H(TPC)		W9HN(TPC)		W9HP(TPC)		D-*****[SMC]							
Valve	(Note 3)		G: Mounting Solenoid valve(Applicable Model) / W:Heater exclude (Not installed)													
			VLAP- / VLBP- / VLAS- / VLBS- / VLAD- / VLBD- / VLAT- / VLSP- / VLSS- / VLB- / VYAP- / VYAS- / VYBP- / VYBS- / VYSP- / VYSS-													

Modified special		[] ※Please consult our technical department.										
w/Solenoid Valve Spec.	size range	016	025	040	050	063	080	100	160	200	250	320
Single acting	[VAⓈS]	Solenoid Valve Spec.	RDV412-5DZ-01			RDS301-5DZ-01A			[Note 4]	Not Available		
Double acting	[VAⓈP]		DS2120-5HZ-01						RDS5120-5DZ-03			
Solenoid valve maker: TPC / Electric power: DC24V												
w/Heater Spec.	size range	016	025	040	050	063	080	100	160	200	250	320
Type: Silicon Rubber Heater		25W	25W	30W	45W	70W	90W	150W	Not Available			
Temperature Max.: Amb.~150℃ / TC.sensor control: K-Type / Electric power: AC220V												

(Note 1) For standard products, use sealing material of vacuum secretion as a FKM (flammable O-ring).

Chemraz® is a registered trademark of Greene, Tweed & Co. Kalrez® is a registered trademark of E.I. du Pont de Nemours and Company.

ULTIC ARMOR® is a registered trademark of NIPPON VALQUA INDUSTRIES, LTD.

(Note 2) Applies only to the double and single operating valves (except VABM-series)

(Note 3) Specifications that are partially changed in standards or standards other than standard products can be specially designed to meet the customer's needs, so please consult with them.

(Note 4) Solenoid valve specification: RDS301-5DZ-02A