

Specification


VL(^A / _B)K series			Vacuum Angle Valve / Double Acting / Bakable type										
			Bellows STEM seal (A: SUS316L / B: AM350)										
Valve port		SIZE	16	25	40	50	63	80	100	160	200	250	320
Flange Standards	ISO-KF	KF	●	●	●	●	●	×	●	×	×	×	×
	ISO-K	KQ	×	×	×	×	●	×	●	×	×	×	×
	ISO-F	KC	×	×	×	×	●	×	●	×	×	×	×
Valve Actuating type			Double acting cylinder										
Fluid			Vacuum in an inert gas system										
Operating temperature °C			≤150[Actuator: Max.60°C]										
Operating pressure Pa (Abs)			1×10 ⁻⁶ ~ to atmospheric pressure										
Conductance L / s ^(Note 1)			7	14	42	95	150	-	520	-	-	-	-
Leakage Pa·m ³ /s	Inside	Standard material (FKM) 1.0×10 ⁻¹⁰ at room temperature (excluding gas permeation)											
	Outside	Standard material (FKM) 1.0×10 ⁻¹¹ at room temperature (excluding gas permeation)											
Main material			Body: SUS304, Bellows: [SUS316L / AM350] Main parts: SUS304, AL-6061, FKM [Standard seal]										
Operating pressure MPa (G)			0.4~0.7										
Operation Port Port Size			PT 1/8" [Rc1/8"]										
Compressed air consumption (@0.5MPa)	cc (mL) ^(Note 2)		22.5	22.5	45	100	185	-	400	-	-	-	-
Open stroke			14	14	18	25	30	-	40	-	-	-	-
Seal distance (A-Value)			40	50	65	70	88	-	108	-	-	-	-
w/Heater Spec.	Size		016	025	040	050	063	080	100	-	-	-	-
Type: Silicon Rubber Heater Jacket	Electric Capacity		25W	25W	30W	45W	70W	90W	150W	Not Available			
Temperature Max.: Amb.~150°C / TC.sensor													
Control: K-Type / Electric power: 220VAC													

(Note 1) Conductance is represented by "molecular flow" of elbow of the same dimension. (Note 2) One stroke condition. (Open & Close)


External dimension table

SIZE	16	25	40	50	63	80	100
A	40	50	65	70	88	-	108
B	151.5	159.5	199.5	224	274	-	332.5
C	48	48	60	69	77	-	98
D	3	3	2	2	5	-	5
F	Ø61	Ø61	Ø78	Ø89	Ø109	-	Ø159
G	PT 1/8"	PT 1/8"	PT 1/8"	PT 1/8"	PT 1/8"	-	PT 1/8"
H	Ø30	Ø40	Ø55	Ø75	Ø95	-	Ø134
J	-	-	-	-	Ø95	-	Ø130
K	-	-	-	-	Ø130	-	Ø165

Dimensional drawing







Internal detail



How to Order

Valve **V(A)B(C)** - ① ② - ③ - ④ - ⑤ ⑥ - (⑦)

Model VLAP - □□□ □□-□□ - □ - □□

Series	A Body shape	VLⓅC	L	L-type(Angle valve) 304SS Body																							
		VYⓅC	Y	Y-type(Inline valve) 304SS Body																							
	B Stem Seal	VAⒶC	A	316L Bellows STEM Seal																							
		VAⓅC	B	AM350 Bellows STEM Seal																							
		VASⒸ	S	O-Ring STEM Seal																							
	C Operation type	VAⓅP	P	Double Acting (Pneumatic)																							
		VAⓅS	S	Single Acting (N.C.)																							
		VAⓅM	M	Manual operation																							
		VAⓅQ	Q	Double Acting, w/Heater (Pneumatic)																							
		VAⓅR	R	Single Acting, w/Heater (N.C.)																							
		VAⓅH	H	Double Acting, Heating model(Pneumatic)																							
		VAⓅK	K	Double Acting, Heating model, w/Heater(Pneumatic)																							
		VLⓅD	D	Double Acting, w/Soft start bypass valve(Pneumatic)																							
		VLⓅT	T	Single Acting, w/Soft start bypass valve(N.C.)																							
		VLⓅX	X	Single Acting, w/Soft start integrated valve(N.C.)																							
		VLⓅW	W	Bonnet gasket seal type, Double Acting (Pneumatic)																							
		VLⓅY	Y	Bonnet gasket seal type, Single Acting (N.C.)																							
		VLⓅZ	Z	Bonnet gasket seal type, Manual operation																							
Port flange	Valve size	①	□□□	016	025	040	050	063	080	100	160	200	250	320													
	Flange Spec.	②	□□ Specific	KF		KQ		KC		CF		JF															
Seal material (Disc, Bonnet, Stem)	③ (Note 1)	□□	N1		ED		S1		FS		R1		R2		R3		P1		P2		U1						
			FKM		NBR		EPDM		VMQ		FFKM		Chemraz®		Chemraz®		Chemraz®		Kalrez®		Kalrez®		ULTIC ARMOR®				
											SS592		SS630		SSE38		4079		9100		UA4640						
			Im case of FFKM (FS), please specify a separate material.																								
CDA port position	④ (Note 2)	□ Branch port Lower part	None		E				S				W														
			Rear		Right				Left				Same Direction														
																											
Sensor	⑤	□	0		1				2																		
			None		1 EA				2 EA																		
Solenoid or Heater Mounting	⑥	□	C		N				P				H														
			W8H(TPC)		W9HN(TPC)		W9HP(TPC)				D-*****[SMC]																
Valve	⑦	(G) or (W)	G: Mounting Solenoid valve(Applicable Model) / W:Heater exclude (Not installed)																								
Valve	(Note 3)		VLAP- / VLBP- / VLAS- / VLBS- / VLAD- / VLBD- / VLAT- / VLSP- / VLSS- / VLBT- / VYAP- / VYAS- / VYBP- / VYBS- / VYSP- / VYSS-																								
Modified special		()	※Please consult our technical department.																								
w/Solenoid Valve Spec.	size range		016	025	040	050	063	080	100	160	200	250	320														
Single acting	[VⒶⓅS]	Solenoid	RDV412-5DZ-01					RDS301-5DZ-01A					(Note 4)	Not Available													
Double acting	[VⒶⓅP]	Valve Spec.	DS2120-5HZ-01												RDS5120-5DZ-03												
Solenoid valve maker: TPC / Electric power: DC24V																											
w/Heater Spec.	size range		016	025	040	050	063	080	100	160	200	250	320														
Type: Silicon Rubber Heater			25W	25W	30W	45W	70W	90W	150W	Not Available																	
Temperature Max.: Amb.~150℃ / TC.sensor control: K-Type / Electric power: AC220V																											

(Note 1) For standard products, use sealing material of vacuum secretion as a FKM (flammable O-ring).

Chemraz® is a registered trademark of Greene, Tweed & Co. Kalrez® is a registered trademark of E.I. du Pont de Nemours and Company.

ULTIC ARMOR® is a registered trademark of NIPPON VALQUA INDUSTRIES, LTD.

(Note 2) Applies only to the double and single operating valves (except VABM-series)

(Note 3) Specifications that are partially changed in standards or standards other than standard products can be specially designed to meet the customer's needs, so please consult with them.

(Note 4) Solenoid valve specification: RDS301-5DZ-02A