

■ BLANK FLANGE / ISO-K

P/N	SIZE	ØA	ØB	T	Dimension
BBLK063	ISO63	95	70.2	12	
BBLK080	ISO80	110	83.2	12	
BBLK100	ISO100	130	102.2	12	
BBLK125	ISO125	155	127.2	12	
BBLK160	ISO160	180	153.2	12	
BBLK200	ISO200	240	213.2	12	
BBLK250	ISO250	290	261.2	12	
BBLK320	ISO320	370	318.2	17	
BBLK400	ISO400	450	400.2	17	

■ BORED FLANGE / ISO-K

P/N	SIZE	ØA	ØB	ØC	a	T	Dimension
BBOK063	ISO63	95	70.2	63.5	5	12	
BBOK080	ISO80	110	83.2	76.3	5	12	
BBOK100	ISO100	130	102.2	101.6	5	12	
BBOK125	ISO125	155	127.2	127.4	5	12	
BBOK160	ISO160	180	153	152.4	5	12	
BBOK200	ISO200	240	213	216.3	5	12	
BBOK250	ISO250	290	261.2	267.4	5	12	
BBOK320	ISO320	370	318.2	318.5	7	17	
BBOK400	ISO400	450	400.2	406.4	7	17	

■ BORED FLANGE / ISO-K(SCH)

P/N	SIZE	ØA	ØB	ØC	a	T	Dimension
BBOK063F	ISO63	95	70.2	76.3	5	12	
BBOK080F	ISO80	110	83.2	89.1	5	12	
BBOK100F	ISO100	130	102.2	114.3	5	12	
BBOK125F	ISO125	155	127.2	139.8	5	12	
BBOK160F	ISO160	180	153	165.2	5	12	
BBOK200F	ISO200	240	213	216.3	5	12	
BBOK250F	ISO250	290	261.2	267.4	5	12	
BBOK320F	ISO320	370	318.2	318.5	7	17	