




■ BLANK FLANGE / ISO-F

P/N	SIZE	ØA	ØB	ØD	n	H	T	Dimension
BBLF063	ISO63	130	70.2	110	4	9	12	
BBLF080	ISO80	145	83.2	125	8	9	12	
BBLF100	ISO100	165	102.2	145	8	9	12	
BBLF160	ISO160	225	153.2	200	8	11	16	
BBLF200	ISO200	285	213.2	260	12	11	16	
BBLF250	ISO250	335	261.2	310	12	11	16	
BBLF320	ISO320	425	318.2	395	12	14	20	
BBLF400	ISO400	510	400.2	480	16	14	20	

■ BORED FLANGE / ISO-F

P/N	SIZE	ØA	ØB	ØC	ØD	n	H	a	T	Dimension
BBOF063	ISO63	130	70.2	63.5	110	4	9	5	12	
BBOF080	ISO80	145	83.2	76.3	125	8	9	5	12	
BBOF100	ISO100	165	102.2	101.6	145	8	9	5	12	
BBOF160	ISO160	225	153.2	152.4	200	8	11	9	16	
BBOF200	ISO200	285	213.2	216.3	260	12	11	9	16	
BBOF250	ISO250	335	261.2	267.4	310	12	11	9	16	
BBOF320	ISO320	425	318.2	318.5	395	12	14	10	20	
BBOF400	ISO400	510	400.2	406.4	480	16	14	10	20	

■ BORED FLANGE / ISO-F(SCH)

P/N	SIZE	ØA	ØB	ØC	ØD	n	H	a	T	Dimension
BBOF063F	ISO63	130	70.2	76.3	110	4	9	5	12	
BBOF080F	ISO80	145	83.2	89.1	125	8	9	5	12	
BBOF100F	ISO100	165	102.2	114.3	145	8	9	5	12	
BBOF160F	ISO160	225	153.2	165.2	200	8	11	9	16	
BBOF200F	ISO200	285	213.2	216.3	260	12	11	9	16	
BBOF250F	ISO250	335	261.2	267.4	310	12	11	9	16	
BBOF320F	ISO320	425	318.2	318.5	395	12	14	10	20	
BBOF400F	ISO400	510	400.2	406.4	480	16	14	10	20	