

■ BLANK & BORED FLANGE / CF-ROTATABLE

P/N	SIZE	ØA	ØE	ØB	ØC	T	T1	T2	H	n	P.C.D	BLANK	BORED
BBLC13HR	CF1.33-BLANK-H	34	19.4			7.3		5.8	4.5	6	27		
BBLC13TR	CF1.33-BLANK-T	34	19.4			7.3		5.8	M4	6	27		
BBOC13HR	CF1.33-BORED-H	34	19.4	19.05	16.6	7.3	4.3	5.8	4.5	6	27		
BBOC13TR	CF1.33-BORED-T	34	19.4	19.05	16.6	7.3	4.3	5.8	M4	6	27		
BBLC21HR	CF2.125-BLANK-H	53.8	26.4			11.9		7.4	6.6	4	41.2		
BBLC21TR	CF2.125-BLANK-T	53.8	26.4			11.9		7.4	M6	4	41.2		
BBOC21HR	CF2.125-BORED-H	53.8	26.4	25.6	23.8	11.9	5.9	7.4	6.6	4	41.2		
BBOC21TR	CF2.125-BORED-T	53.8	26.4	25.6	23.8	11.9	5.9	7.4	M6	4	41.2		
BBLC27HR	CF2.75-BLANK-H	69.5	39			12.7		7.2	6.6	6	58.7		
BBLC27TR	CF2.75-BLANK-T	69.5	39			12.7		7.2	M6	6	58.7		
BBOC27HR	CF2.75-BORED-H	69.5	39	38.1	35.7	12.7	5.7	7.2	6.6	6	58.7		
BBOC27TR	CF2.75-BORED-T	69.5	39	38.1	35.7	12.7	5.7	7.2	M6	6	58.7		
BBLC33HR	CF3.375-BLANK-H	86	51.5			17.5		9.5	8.6	8	72.4		
BBLC33TR	CF3.375-BLANK-T	86	51.5			17.5		9.5	M8	8	72.4		
BBOC33HR	CF3.375-BORED-H	86	51.5	50.8	47.8	17.5	7.5	9.5	8.6	8	72.4		
BBOC33TR	CF3.375-BORED-T	86	51.5	50.8	47.8	17.5	7.5	9.5	M8	8	72.4		
BBLC45HR	CF4.5-BLANK-H	113.5	64.5			19		12.7	8.6	8	92.1		
BBLC45TR	CF4.5-BLANK-T	113.5	64.5			19		12.7	M8	8	92.1		
BBOC45HR	CF4.5-BORED-H	113.5	64.5	63.5	60.5	19	10.7	12.7	8.6	8	92.1		
BBOC45TR	CF4.5-BORED-T	113.5	64.5	63.5	60.5	19	10.7	12.7	M8	8	92.1		
BBLC06HR	CF6-BLANK-H	152	103			21.5		14.3	8.6	16	130.2		
BBLC06TR	CF6-BLANK-T	152	103			21.5		14.3	M8	16	130.2		
BBOC06HR	CF6-BORED-H	152	103	101.6	97.6	21.5	11.3	14.3	8.6	16	130.2		
BBOC06TR	CF6-BORED-T	152	103	101.6	97.6	21.5	11.3	14.3	M8	16	130.2		
BBLC08HR	CF8-BLANK-H	203	154			24		15.8	8.6	20	181		
BBLC08TR	CF8-BLANK-T	203	154			24		15.8	M8	20	181		
BBOC08HR	CF8-BORED-H	203	154	152.4	148.4	24	12.8	15.8	8.6	20	181		
BBOC08TR	CF8-BORED-T	203	154	152.4	148.4	24	12.8	15.8	M8	20	181		
BBLC10HR	CF10-BLANK-H	254	206			25		17.2	8.6	24	231.8		
BBLC10TR	CF10-BLANK-T	254	206			25		17.2	M8	24	231.8		
BBOC10HR	CF10-BORED-H	254	206	203.2	199	25	12.2	17.2	8.6	24	231.8		
BBOC10TR	CF10-BORED-T	254	206	203.2	199	25	12.2	17.2	M8	24	231.8		
BBLC12HR	CF12-BLANK-H	304	256			28.6			8.6	32	284		
BBLC12TR	CF12-BLANK-T	304	256			28.6			M8	32	284		
BBOC12HR	CF12-BORED-H	304	256	254.6	250.8	28.6	15.6	20.6	8.6	32	284		
BBOC12TR	CF12-BORED-T	304	256	254.6	250.8	28.6	15.6	20.6	M8	32	284		
BBLC14HR	CF14-BLANK-H	355.6	270			28.5			10	30	325.4		
BBLC14TR	CF14-BLANK-T	355.6	270			28.5			M10	30	325.4		
BBOC14HR	CF14-BORED-H	355.6	270	267.8	263.8	28.5	12.6	19.6	10	30	325.4		
BBOC14TR	CF14-BORED-T	355.6	270	267.6	263.8	28.5	12.6	19.6	M10	30	325.4		

